

florprotec® - TacBac Clear

florprotec®

TECHNICAL DATA SHEET FLORPROTEC TACBAC CLEAR

BASE MATERIAL & FEATURES

Tacbac Clear is manufactured from polyethylene and coated on one side with a water based adhesive. The product is inside wound and is manufactured at 50 microns. Available as flat film or with embossed anti-slip finish.

FLAME RETARDANT DETAILS

BSAU169 (ISO3795) – burning resistance requirements, flammability testing – pass.

APPLICATIONS

- Use on carpet only. (not for smooth surfaces).
- Apply to clean and dry carpets, free from dust and excessive loose fibres.
- Avoid stretching the film when applying
- Press Tacbac Clear firmly onto carpet using a weighted roller (Tacbac applicator)
- Allow time for sub floor vapours / adhesives to evaporate before applying Tacbac Clear (this refers to vapours from newly glued down carpets and underlay).
- Tacbac Clear can be used for periods up to 8 weeks, for longer remove and renew.

Caution

- Never place Tacbac Clear on a wet or damp carpet.
- Avoid trapping vapours.
- Tacbac carpet cover should not be used on deep pile domestic carpets, similar to Saxony style products or any deep pile carpet.
- Applying to used carpets is a risk area, particularly on soiled, contaminated or poor condition carpets. Our guidelines and cautions are to assist the user in minimising their risk.
- Do not use on smooth finishes, for carpets only

ADVANTAGES

PRODUCT DETAILS

| Product Code | Width | Length | Weight | Colour |
|--------------|--------|--------|--------|--------|
| T73 | 600mm | 100m | 4kg | Clear |
| T37 | 600mm | 100m | 4kg | Clear |
| T37/50 | 600mm | 50m. | 2.2kg | Clear |
| T5308 | 800mm | 100m | 6kg | Clear |
| T59 | 100mm | 100m | 7kg | Clear |
| T41 | 1200mm | 100m | 8kg | Clear |
| T51 | 600mm | 25m | 1kg | Clear |
| Antislip | 600mm | 100m | 4kg | Clear |

